FLUENT - Turbulent Pipe Flow (LES)

Author: Ranjith Tirunagari, Cornell University Problem Specification 1. Pre-Analysis & Start-Up 2. Geometry 3. Mesh 4. Physics Setup 5. Numerical Solution 6. Numerical Results 7. Verification & Validation Exercises Comments

Turbulent Pipe Flow (LES)

Created using ANSYS 13.0

Problem Specification

Consider fluid flowing through a cylindrical pipe of diameter D = 0.0127 m and length L = 5D = 0.0635 m. The bulk velocity at the pipe inlet is $U_{bulk} = 6.58 \text{ m}$ /s. Let us consider the case where the density of the fluid is constant. Take density $= 1.331 \text{ kg/m}^3$ and coefficient of viscosity $\mu = 2.34 \times 10^{-5} \text{ kg/(ms)}$. The Reynolds number *Re* based on the pipe diameter and the bulk velocity is

$$\operatorname{Re} = \frac{\rho U_{bulk} D}{\mu} \approx 4750$$

Solve the above fluid flow problem using the LES capability in FLUENT via ANSYS Workbench. Plot the mean and the root mean square velocities versus the radial distance at a particular x/D downstream of the inlet. Compare the mean velocity obtained from the LES simulation with the mean velocity obtained using the k- model.

Go to Step 1: Pre-Analysis & Start-Up

Go to all FLUENT Learning Modules