

Bike Crank (Part 2) - Numerical Results

Author: Sebastien Lachance-Barrett, Cornell University

Problem Specification

1. Pre-Analysis & Start-Up

2. Geometry

3. Mesh

4. Physics Setup

5. Numerical Solution

6. Numerical Results

7. Verification & Validation

Exercises

Comments

Numerical Results

Here, we find the strain of each surface bodies along their lengths. We do this using the local coordinate system of each gauge which is given to us from the elemental triad solution.

Summary of steps in the above video:

1. Right click on Solution the tree > Strain > Normal
2. For geometry > select leftmost strain body > Apply
3. For Orientation > x axis (can look at elemental triad system)
4. Change Global System to Solution System
5. Right Click Solution > Evaluate All Results



The video mentions that you need to pay attention to the sign of the strain value only, not the direction of the coordinate system. For example, you should not be concerned, if say, the x-direction for one of your gauge points in the opposite direction of the other two gauges in the rosette. This is because the strain transformation is invariant when you rotate a coordinate direction by 180 deg. The transformation formula, shown below, has $\cos(2)$ and $\sin(2)$. When $\theta = 180$ deg, $\cos(2)$ and $\sin(2)$ will be the same as when $\theta = 0$.

$$\left\{ \begin{array}{l} \varepsilon_{x'} = \frac{\varepsilon_x + \varepsilon_y}{2} + \frac{\varepsilon_x - \varepsilon_y}{2} \cos 2\theta + \varepsilon_{xy} \sin 2\theta \\ \varepsilon_{y'} = \frac{\varepsilon_x + \varepsilon_y}{2} - \frac{\varepsilon_x - \varepsilon_y}{2} \cos 2\theta - \varepsilon_{xy} \sin 2\theta \\ \quad = \varepsilon_x + \varepsilon_y - \varepsilon_{x'} \\ \varepsilon_{x'y'} = -\frac{\varepsilon_x - \varepsilon_y}{2} \sin 2\theta + \varepsilon_{xy} \cos 2\theta \end{array} \right.$$

For more information on transformations, [see this link](#).

[Go to Step 7: Verification & Validation](#)

[Go to all ANSYS Learning Modules](#)