

User Defined Functions - Numerical Solution

Authors: Lara Backer and Rajesh Bhaskaran, Cornell University

[Problem Specification](#)

[1. Pre-Analysis & Start-Up](#)

[2. Geometry](#)

[3. Mesh](#)

[4. Physics Setup](#)

[5. Numerical Solution](#)

[6. Numerical Results](#)

[7. Verification & Validation](#)

[Exercises](#)

[Comments](#)

Numerical Solution

A UDF is needed to calculate the lift force over the entire cylinder by integrating the pressure over cylinder segments set to "wall" or "velocity inlet". We cannot use the in-built lift calculator for this case because it does not consider segments set to "velocity inlet." **Important point to keep in mind: The UDF only affects the post-processing of the lift coefficient. It does NOT change the base numerical solution.** The strategy for computing the lift force using the UDF is as follows:

1. Turn on a 'user defined scalar' which Fluent will solve for
2. On the cylinder surface, set the below equation by implementing the UDF as a boundary condition for

$$C = -p \sin(\theta) \quad (1)$$

3. Run at least one iteration to integrate over the cylinder surface

Note that the liftFunc UDF calculates a side force that is NOT normalized. So you'll have to divide the reported value by $0.5 \cdot \rho \cdot v^2 \cdot D$ to get the normalized side force. This is because when you integrate liftFunc, you get the integral of $-p \cdot \sin(\theta)$ on the chosen surfaces.

User-defined function implementation to obtain the lift coefficient around the cylinder is as follows.

[Go to Step 6: Numerical Results](#)

[Go to all FLUENT Learning Modules](#)