

# AIM Heat Conduction in a Bar - Pre-Analysis

Author(s): Sebastian Vecchi, ANSYS Inc

## Problem Specification

1. Pre-Analysis & Start-Up
2. Geometry
3. Mesh
4. Physics Setup
5. Results

## Pre-Analysis

### Equations

The governing equation for heat transfer rate for a rectangular bar, as generalized by Fourier in 1807, is the following equation. In this equation,  $k$  is the proportionality factor as a function of material and temperature,  $A$  is the cross-sectional area and  $L$  is the length of the bar.

$$Q = kA \frac{(T_A - T_B)}{L} = -kA \frac{(T_A - T_B)}{L} = -kA \frac{dT}{dx}$$

The equation above can be written in terms of heat flux using the definition that heat flux is the amount of heat transfer per unit area. This one-dimensional form of Fourier's law of heat conduction is found below.


$$q' = -k \frac{dT}{dx}$$


A few words on the formatting on the following instructions:

1. Notes that require you to perform an action are colored in blue
2. General information will be colored in black, but do not require any action
3. Words that are **bolded** are labels for items found in ANSYS AIM
4. Most important notes will be colored in red

### Start-Up

Now that we have the pre-calculations, we are ready begin simulating in ANSYS AIM. [Open ANSYS AIM by going to Start > All Apps > ANSYS 18.1 > ANSYS AIM 18.1](#). Once you are at the starting page of AIM, [select the Thermal template](#) as shown below.



 **Thermal: Physics**


Additional physics:

☐ Structural

☐ Electric conduction

☐ Fluid flow

Calculation type:

☒ **Steady/static** 


☐ Time-dependent


Options:

☐ Compute fatigue results

Typical settings and results will be defined automatically.

You will be prompted by the **Thermal** template to either **Define new geometry**, **Import geometry file**, or **Connect to active CAD session**. Select **Define new geometry** and press **Next**.



 **Thermal: Physics**


Additional physics:

☐ Structural

☐ Electric conduction

☐ Fluid flow

Calculation type:

☒ **Steady/static** 


☐ Time-dependent


Options:

☐ Compute fatigue results

Typical settings and results will be defined automatically.

For this problem, we will be using the default **Steady/static** calculation type. Press **Finish**. No additional physics are necessary.



 **Thermal: Physics**


Additional physics:

☐ Structural

☐ Electric conduction

☐ Fluid flow

Calculation type:

☒ Steady/static 

☐ Time-dependent

Options:

☐ Compute fatigue results

Typical settings and results will be defined automatically.

The **Model Editor** will launch automatically. In order to use the units given to us in the problem, [press the Project button](#) in the top left corner and [select Units > US Customary](#).

[Go to Step 2: Geometry](#)

[Go to all ANSYS AIM Learning Modules](#)