ANSYS AIM 3D Static Force Computation - Pre-Analysis & Start-Up

Author(s): Joshua Wallace & Steve Scampoli, ANSYS Inc.

- Problem Specification
- 1. Pre-Analysis & Start-Up
- 2. Geometry
- 3. Physics Setup
- 4. Solution/Results

Pre-Analysis & Start-Up

Governing Equation

Magnetostatics is the study of magnetic fields in devices where the magnetic field is generated from DC (steady) currents and/or permanent magnets. Magnetostatics is a special case of Maxwell's equations, which form the basis of electromagnetism.

For magnetostatics the electric field inside of a current carrying coil is completely decoupled from the magnetic field, and the following Maxwell's equations are solved for magnetostatics -

 $\nabla \times \boldsymbol{H} = \boldsymbol{J}$ $\nabla \cdot \boldsymbol{B} = 0$

$\boldsymbol{B} = \mu_0 \mu_r(\boldsymbol{H}) \cdot \boldsymbol{H}$

Where denotes divergence, H is the magnetic field intensity, J is the current density and B is the magnetic flux density.

Start-Up

A few words on the formatting on the following instructions:

- 1. Notes that require you to perform an action are colored in blue
- 2. General information will be colored in black, but do not require any action
- 3. Words that are **bolded** are labels for items found in ANSYS AIM
- 4. Most important notes will be colored in red

Now that the pre-calculations are finished, we are ready to begin the simulation in ANSYS AIM. Open ANSYS AIM by going to Start > All Apps > ANS YS 18.2 > ANSYS AIM 18.2. Once starting page has opened, select the Magnetics template as shown below.



AlM will prompt by the Magnetics template to either Define new geometry, Import geometry file, or Connect to active CAD session. Select Import geometry file, press Next.

Go to Step 2: Geometry

Go to all ANSYS AIM Learning Modules