ANSYS Compressible Flow over a Wing-Body Junction - Mesh

Author(s): Sebastian Vecchi, ANSYS Inc.

Problem Specification

1. Start-Up

2. Geometry

3. Mesh

4. Physics Setup


5. Solution/Results

Mesh

Once you have exited the modeling window, initiate the meshing process by clicking on **Mesh** in the workflow. If desired, In the **Choose display mode** menu near the top of the model window, select **Translucent display** to view what is going on inside the enclosed volume.

Set Mesh Size & Controls

Drag the **Mesh resolution** slider to the second highest setting. Uncheck the **Use predefined settings** button and input 10 [degree] for the **Curvature normal angle** under **Global Sizing**.



AIM will prompt you to fix airplane body.	k the boundary layer before genera	ting the mesh. Click on Boun d	dary Layer under Mesh Contro	s. Select all of the faces of the
Dan anata Maab				
Generate Mesh	l el, then click Generate Mesh unde	r Quitnut or at the top of the co	proon by the status window for M	lock AIM will detect that you
eady to generate the mo	esh and highlight the buttons in blu	e.	creen by the status willdow for iv	esii. Aiwi wiii delect triat you

Go to Step 4: Physics Setup

Go to all ANSYS AIM Learning Modules