# 3D Bifurcating Artery (steady) - Pre-Analysis & Start-Up

Author(s): Keith Works, Cornell University

Problem Specification 1. Pre-Analysis & Start-Up

- 2. Geometry
- 3. Mesh
- 4. Physics Setup
- 5. Numerical Solution
- 6. Numerical Results
- 7. Verification & Validation
- 8. Exercises

## Pre-Analysis & Start-Up

## **Pre-Analysis**

In the Pre-Analysis step, we'll review the following:

- Governing Equations: We will review the governing equations that need to be solved in this problem.
- Boundary Conditions: We will go into more details about the boundary conditions that are applied in this problem.

## **Governing Equations**

Before starting a CFD simulation, it is always good to take a look at the governing equations underlying the physics. In this case, although we have additional complexities such as pulsatile flow and non-newtonian fluids, the governing equations are the same as any other fluids problem. The most fundamental governing equations are the continuity equation and the Navier-Stokes equations. Here, let's have a quick review of the equations. Continuity Equation:

$$\frac{\partial \rho}{\partial t} + \nabla \cdot (\rho \mathbf{v}) = 0$$

However, since we are considering only the steady case, the time-dependent term is zero. Thus, the continuity equation above can be further simplified in the form below:

 $\nabla \cdot \mathbf{v} = 0$ 

The Navier-Stokes Equation is written as follows:

$$\rho(\mathbf{v} \cdot \nabla \mathbf{v}) = -\nabla p + \rho \nabla^2 \mathbf{v} + \mathbf{f}$$

## **Boundary Conditions**

### Wall:

The easiest boundary condition to determine is the artery wall. We simply need to define the wall regions of this model and set it to "wall". From a physical viewpoint, the "wall" condition dictates that the velocity at the wall is zero due to the no-slip condition.

#### Inlet:

Here our inlet velocity will be a constant 0.315 m/s. This was chosen to give us a Reynolds number of 600.

#### Outlets:

The systolic pressure of a healthy human is around 120 mmHg and the diastolic pressure of a healthy human is around 80 mmHg. Thus taking the average pressure of the two phases, we use 100 mmHg (around 13332 Pascal) as the static pressure at the outlets.

#### Go to Step 2: Geometry

Go to all FLUENT Learning Modules